**₿EPA** 

### United States Environmental Protection Agency

# WELL REWORK RECORD, PLUGGING AND ABANDONMENT PLAN, OR PLUGGING AND ABANDONMENT AFFIDAVIT

		<u>R PLUGGING AND A</u>	BANDONMENT	AFFIDAVIT			
Merit Energy C 13727 Noel Ros Dallas, TX 752 972-628-1441	ad, Suite 1200	Permittee					
Permit or EPA ID	Number	API Number	Full	Well Name			
WY20000-021	79	49-013-06839	Shos	shone 65-41			
State		County					
Wyoming		Fremo	<u> </u>				
Locate well in tw Surface Location SW 1/4 of		of quarter section and drilling uni	Latitude 43.53363				
41.111	from (N/S) S Line of quar from (E/W) E Line of quar						
Well Class	Timing of Action (pick one)	~~~~	······	Type of Action (pick one)			
Class I	Notice Prior to Work		7	Well Rework			
✓ Class II	Date Expected to Comm	Date Expected to Commence					
Class III	Report After Work			Conversion to a Non-Injection Well			
Class V	Date Work Ended 6/7/	2022		Conversion to a Non-injection were			
Merit Energy	Company submits the attach	ned daily reports and wellbor	e diagram following pluç	g and abandonment operations.			
attachments information	s and that, based on my inquiry o	Certification  personally examined and am famine the second secon	llar with the information sub esponsible for obtaining the	e information, I believe that the			
	I Title (Please type or print)	Signature		Date Signed			
š	Senior Regulatory Analyst		Lawy your	06/21/2022			
		- Call	they/				

EPA Form 7520-19 (Rev. 4-19)

#### **INSTRUCTIONS FOR FORM 7520-19**

This form replaces forms 7520-12 and 7520-14. Use this form only when work is planned or has occurred that affects the well's construction or operation as an injection well, including work on the casing, tubing or packer (or for shallow Class V wells, the subsurface fluid emplacement network). Use one form per injection well. While reports or other information developed by contractors or service companies may be attached, this form must be signed by a responsible entity as described at 40 CFR 144.32. Note: operators closing Class V wells should use Form 7520-17.

NAME, ADDRESS, PHONE AND/OR EMAIL OF PERMITTEE: Enter the name and street address, city/town, state, and ZIP code of the permittee. Also provide an email address (if available) and/or a phone number.

PERMIT OR EPA ID NUMBER: Enter the well identification number or permit number assigned to the well by the EPA or the permitting authority.

API NUMBER: Enter the number assigned by the local jurisdiction (usually a State Oil and Gas Agency) using the American Petroleum Institute standard numbering system.

FULL WELL NAME: Enter the full name of the well or project.

Enter the STATE and COUNTY where the well is located. For States that do not have counties, use the name of that State's equivalent jurisdiction at a more local level.

WELL LOCATION: Fill in the complete township, range, and section to the nearest quarter-quarter section. A township is north or south of the baseline, and a range is east or west of the principal meridian (e.g., T12N, R34W). Also include the distance, in feet, from the nearest north or south line and nearest east or west line of the quarter-section. Also, enter the latitude and longitude of the well in decimal degrees, to five or six places if possible; be sure to include a negative sign for the longitude of a well in the Western Hemisphere and a negative sign for the latitude of a well in the Southern Hemisphere.

Enter the WELL CLASS, i.e., the class of injection well as defined in 40 CFR 144.6.

TIMING OF THE ACTION: Check *Notice prior to work* if the activity has not yet occurred (i.e., is planned). Check *Report after work* if the activity described has already occurred. As appropriate, include the date the activity is expected to start or the date the activity was completed. (Note this may not be available, e.g., for a plugging plan submitted with a permit application.)

TYPE OF ACTION: Check the appropriate box to describe the kind of activity being reported. Check *Well Rework* for work that was/will be performed on the well after it has already been in operation as an injection well. Check *Plugging and Abandonment* to report on plans for or descriptions of final closure/plugging after use as an injection well. Check *Conversion to a Non-injection Well* if the well is to be converted to something other than an injection well.

Provide a NARRATIVE DESCRIPTION of the work planned to be performed, or that was performed. The narrative should include a description of the main procedures planned or that occurred during the work activity. A service company report, daily report, or similar document may be attached if it includes all the requested information and is clear and legible.

For well reworks, include the following information: The reason for the well rework; depths of activity; type of activity; changes to injection well configuration, well casing, or cement behind casing; any plug added to the well and its depth; any newly drilled interval and its depth; method(s) to demonstrate that the well has mechanical integrity (as applicable); and any deviations from the approved rework plan (as applicable).

For a well plugging plan, include the following information: Reason for the well plugging; number of plugs placed, and their depths; materials used as plugs (e.g., cast iron bridge plug, cement, cement retainer); method to set plugs; and wait-on-cement times, if any. Also provide one or more cost estimates from an independent firm in the business of plugging and abandoning wells to plug the well as described in the plan.

For well plugging affidavit, include the following information: Reason for the well plugging; number of plugs placed, and their depths; materials used as plugs (e.g., cast iron bridge plug, cement, cement retainer); method to set plugs; wait-on-cement times, if any; and any deviations from the approved plugging plan (if applicable).

For conversion to a non-injection well, include the following information: Depths of activity; type of activity; changes to injection well configuration, well casing, or cement behind casing; any plug added to the well and its depth; any newly drilled interval and its depth; depths of new perforations; and method(s) to demonstrate that the well has mechanical integrity (as applicable).

For all of the above activities, include a well sketch depicting the work, results of well tests/logging performed, service company tickets, and any other available information demonstrating how the work was/is to be performed. Also, specify whether depths are below ground surface, relative to Kelly bushing, etc.

**CERTIFICATION:** This form must be signed and dated by either: a responsible corporate officer for a corporation, by a general partner for a partnership, by the proprietor of a sole proprietorship, or by a principal executive or ranking elected official for a public agency.

PAPERWORK REDUCTION ACT NOTICE: The public reporting and recordkeeping burden for this collection of information is estimated to average between 6.0 and 7.9 hours per response, depending on the injection well class. Burden means the total time, effort, or financial resource expended by persons to generate, maintain, retain, or disclose or provide information to or for a Federal Agency. This includes the time needed to review instructions; develop, acquire, install, and utilize technology and systems for the purposes of collecting, validating, and verifying information, processing and maintaining information, and disclosing and providing information; adjust the existing ways to comply with any previously applicable instructions and requirements; train personnel to be able to respond to the collection of information; search data sources; complete and review the collection of information; and, transmit or otherwise disclose the information. An agency may not conduct or sponsor, and a person is not required to respond to, a collection of information unless it displays a currently valid OMB control number. Send comments on the Agency's need for this information, the accuracy of the provided burden estimates, and any suggested methods for minimizing respondent burden, including the use of automated collection techniques to Director, Collection Strategies Division, U.S. Environmental Protection Agency (2822), 1200 Pennsylvania Ave., NW., Washington, D.C. 20460. Include the OMB control number in any correspondence. Do not send the completed forms to this address.

## WellView<sup>.</sup>

## **Daily Operations Report**

Report Date: Report #

Well Name: Shoshone 65 41

Daily Operations									
Peport Start Date:	Primary Activity								
4/27/2022 Department									
MORU, Dig out around well head to put down front pads. SDFN Report Start Date	Primary Asilvity								
4/28/2022	and the second s								
perations Summary  ND flowline, RU workfloor and tongs. Release R-4 pkr. Spot in trailer. Began to swab casing while pulling pkr. Haul vac trailer and hook up to backside csg valve.  D 38 jts 2?" tbg to TOH. LD pkr. Secure well w/ last jt. PU tools/location. RDMO:									
Report Start Date 6/2/2022	Primary Activity								
Operations Summary MIRU									
Report Start Date 6/3/2022	Primary Activity								
Operations Summary  Spot in equipment, N/D well head, N/U BOP, R/U work floor, Spot in work string & ts & stand back 19 stands & 1 single, L/D B&S, SIW, SDFN.	tally tbg, P/U 4 1/2 B&S, TIH w/ 41 jts of 2 3/8 tbg & 4 1/2 B&S @ 1266', L/D 2								
Report Start Date 5/6/2022	Primary Activity								
Operations Summary P/U 4 1/2 CICR, TIH w/ 39 jts & set @ 1206', R/U pump truck, Tie onto tbg & roll h 10 min test passed, Sting into CICR & est injection rate w/ 3 bbl/min @ 250 psi, N sx on top, L/D 8 jts, Mix & pump 7 bbls of 9 ppg mud from 954'-500', L/D 15 jts, C calance plug from 495'-50' from surface instead of shooting perfs & pumping cem sx of cement form 495'-50' from surface, L/D 16 jts, Did not rig down due to wind,	fix & pump 41 sx of cement below w/ 3 bbl/min @ 150 psi, Sting out & spot 10 onsult w/ Jonas Wolfe w/ the BLM & amend procedure as follows Spot cement ent around due to no surface csg & 5 1/2 csg being cemented, Mix & pump 35								
Report Start Date 5/7/2022	Primary Activity								
operations Summary RDMOSU, N/D BOP, Dig up around well head, Cut off 5 1/2 x 4 1/2 csg 3' BGL, R was cemented to surface, Weld on plate w/ well legals & backfill, Dig up anchors 8									

# WellView

www.peloton.com

## Schematic - Current

Well Name:	: Shosh	one 65 41											
API/UWI 490130683900					Liconoc #			Well Configuration Type					
Original KB Elevation (ft) 7,206.00		K6-Tubing Head Distance (ft) Original Spud Date 7,206.00 1/1/1900 00:00			Rig Release Date		PRTC (All (RKB)	Total Depth All (TVD) (ffKB)					
Most Recent Jo	)b	Primary Job Type		Secondary Job Type		Job Start Date		Job End Date					
Plug & Abandor	<u> </u>	Permanently Abandon	Well			4/27/2022							
TD: 1,706.0 SHOSHONE-65 41, 6/21/2022 10:34:47 AM													
MD (ftKB)	Vertical schematic (actual)												
11.2	S. S	STAIN NATIONALIA	EK ANAAN EUN EN	1.588.833.8348.13348.848.843		1855,08,08163855,083		a Alama in Dimmandi menya mengeliken ingilika ingini dia belanggian					
14.1	Cement Plug; 14.0-50,0; 6/7/2022												
49.9	Cement Plug; 50,0-495,0; 6/6/2022												
432.1	Production Casing Cement; 14.0-1,261.0; 3/13/1986; 55 sxs cement class "G" plus 2% CaCl2. Had 8												
495.1		Casing Joints; 4 1/2; 4.00; 14.0-1,261.0; 1,247.00 p PPG MUD; 500.0-954.0; 6/6/2022											
500.0		Casing Joints; 5 1/2; 5.01; 14.0-1,693.0; 1,679.00											
954.1	Cement Plug; 954.0-1,206.0; 6/6/2022  Production Casing Cement, 432.0-1,706.0; 11/15/1954; 100 sacks of stratolite cement. Opened two												
1,206.0		stage collar at 1267'. Cemented with 90 sacks of ideal regular cement. Full returns to surface while cementing. Cement top at 432' by calculation.											
1,208.0		Cement Retainer; 1,206.0-1,208.0; 6/6/2022 Cement Plug; 1,208.0-1,261.0; 6/6/2022											
1,261.2		J	Cen	ent Plug; 1,261,0	-1,406.0; 6/6/202	22							
1,308.1		PERFORATED; 1,308.0-1,320.0; 1/28/1986; Rigged up Petro-Log. Ran in hole w/GR-CCL to 1,360'; could not get below 1,360'. Logged to 100'. Pulled out of hole. Picked up perfig gun. Ran in hole and											
1,319.9			new		iting nipple and N	/lodel "AD-1"		ed down Petro-Log, Picked up and set packer @ 1,212,31					
1,335.0			PER coul	FORATED; 1,335 d not get below 1,	.0-1,356.0; 1/28/ 360'. Logged to	1986; Rigged 100', Pulled o	ut of hole. Picked up	in hole w/GR-CCL to 1,360'; perfig gun. Ran in hole and					
1,356.0			new		iting nipple and N	/lodel "AD-1"		ed down Petro-Log. Picked up and set packer @ 1,212.31					
1,379.9			XACII	); 1,380.0-1,406.0	; 3/20/1958		1/2" casing 1544 to	: 1549' - 30 hole, 1585-1630' -					
1,405.8								45 to 1660 w/ 750 gallons					
1,490.2			Brid	qe plug - permane	int; 1,490.0-1,49	2.0; Drilled on	BP and pushed to 1	1490' after running liner.;					
1,492.1				/1986			·						
1,544.0			<b>80000</b>	); 1,380.0-1,660.0 FORATED: 1.544		1986: Perf 5	1/2" casing 1544 to 1	1549' - 30 hole, 1585-1630' -					
1,548.9			210	hole, 1645-1660' -	- 90 hole. Total o			15 to 1660 w/ 750 gallons					
1,585.0	-	ACID; 1,544.0-1,620.0; 3/20/1958 ACI : 1,544.0-1,630.0; 11/20/1954 RESECTION OF A 500.0 A 500.0 A 500.0 Dayle 4 500.0 A 500.0											
1,620.1			1000000 T	HORATED; 1,585 hole, 1645-1660' -	.0-1,630.0; 3/15/ - 90 hole. Total o	1986; Perf 5 f 330 17/32" b	1/2" casing 1544 to oullets. Acidizing 164	1549' - 30 hole, 1585-1630' - 15 to 1660 w/ 750 gallons					
1,629.9			(2000										
1,645.0		ACID; 1,645.0-1,660.0; 11/20/1954 PERFORATED; 1,645.0-1,660.0; 3/15/1986; Perf 5 1/2" casing 1544 to 1549' - 30 hole, 1585-1630' -											
1,660.1								1549 - 30 noie, 1565-1630 - 15 to 1660 w/ 750 gallons					
1,674.9	Production Casing Cement (plug); 1,675.0-1,706.0; 11/15/1954; 100 sacks of stratolite cement. Opened two stage collar at 1267'. Cemented with 90 sacks of ideal regular cement. Full returns to surface while												
1,706.0			<u> </u>	enting, Cement to SHOSHONE-65									

Page 1/1

Report Printed: 6/21/2022